







VRLA Battery **SPB 12-100**

Specifications

Nominal Voltage	12 V				
Rated Capacity (25 °C)	20hr Rate (1,80V/cell)	10hr Rate (1,80V/cell)	5hr Rate (1,70V/cell)	1hr Rate (1,60V/cell)	
	106 Ah	100 Ah	89 Ah	63 Ah	
Dimensions (mm) & Weight (kg)	Length	Width	Height	Overall Height	Weight
	330mm	171mm	215mm	220mm	32 kg
Number / Type of Terminals	2 / M6				

Technical Characteristics

Design Life at 20°C	10-12 years
Eurobat Classification	High Performance
Internal Resistance (Fully charged - 25°C)	5 mΩ
Short-circuit current	2100 A
Max Charging Current	30 A
Min safe end Discharge Voltage	1,60 V/cell
Self discharge per month at 20°C	3%
Recommended Charging Voltage at 20°C	Stand-by use (V/cell): 2,25 to 2,30 Cycle use (V/cell): 2,40 to 2,50
Container Material	ABS-UL94 HB
Electrolyte Type	Sulfuric Acid
Type of plates / Alloy	Flat plates / Lead-Calcium-Tin alloy
Type of Separator	Absorbant Glass Mat
Valve Type / Operational Pressure	Rubber / 1-3 psi (70-200 mbar)
Operating Temperature Range	-20 to + 50°C
Storage time at 20°C	9 months



EPS Electric Power Systems GmbH
Erlengasse 540
A-3034 Maria Anzbach Austria
Tel. +43 (0) 2772 56150
Fax +43 (0) 2772 56150 20
info@eps.at www.eps.at
www.it-usv.at

SUNLIGHT
creating energy