

■ Datasheet: El. Main branch term., 4 pole, 80A, in. 1x16mm², out. 2x6mm²



IKB04016

■ SCHRACK-INFO

Article-description: El. Main branch term., 4 pole, 80A, in. 1x16mm², out. 2x6mm²

■ Assembly details

Mounting on DIN-rail or on base plate. Time savings in cabling and approximately 80% space savings. Modular construction, 1-4 pole Systems can be built with several blocks.

■ Technical data

	Material	Colour
Clamping body	Brass	Plain
Housing	PA66-V0	grey
Housing body	PC-V2	clear
Hexagon socket set screw	Steel	Zn-Plated

■ General data

Heat deflection temp.	PA66 ? 140°C / PC ? 120°C
Comparative tracking index	PA66 = 600V / PC = 300V
Standard	IEC 60 947 -7 - 1

■ Electrical data

	IEC
max. electrical load	80A
max. operating voltage	690V
Protection	IP20
Short circuit withstand	I _{pk} 21,6kA / I _{cw} 1s 3kA

■ Cross section


	U - single wire	K - fine wire (with sleeve)	Torque
	R - multi wire	F - fine wire (with sleeve)	
	Incomer		
1 x Ø6,8mm	2,5mm ² - 16mm ² 14 AWG - 6 AWG	2,5mm ² - 10mm ² 14 AWG - 8 AWG	1,5Nm 13.2 lbf.in
	Outgoings		
8 x Ø5,7mm	1,5mm ² - 10mm ² 16 AWG - 8 AWG		1,5Nm 13.2 lbf.in

■ Approval and Marking

The products are CE conform and correspond to the RoHS of the EU.

■ Datasheet: El. Main branch term., 4 pole, 80A, in. 1x16mm², out. 2x6mm²

■ Dimensional drawing



■ Models

Description	Order No.
El. Main branch term., 4 pole, 80A, in. 1x16mm ² , out. 2x6mm ²	IKB04016